

City of Victorville Department of Development Planning * Building * Code Enforcement

14343 Civic Drive PO Box 5001 Victorville, CA 92393-5001 (760) 955-5135 Fax (760) 269-0070 planning@victorvilleca.gov

Greenhouse Gas Emissions Screening Table Review

Note: This form is to be used only for projects which are subject to CEQA and not exempt from CEQA (i.e. Negative Declaration, Mitigated Negative Declaration or Environmental Impact Report).

GENERAL INFORMATION	
Applicant:	Contact Name:
Address:	
Telephone No.: E	Email Address:
TYPE OF PROJECT	
Residential (Single-Family or Multi-Family)	☐ Commercial or Industrial
PROJECT LOCATION	
General Location/Address of Project:	
Name of Business (if applicable):	
Assessor's Parcel No(s):	
Existing Zoning:	
PROJECT DESCRIPTION:	
Instructions	

- 1. Fill out the appropriate section below for either Residential or Commercial/Industrial.
- 2. Choose items which the proposed project will incorporate into the development to reach a minimum of 100 points.
- 3. Do not choose items which are independently required by other laws, codes or the VVMC, such as the California Building Code, the Civic Center Sustainability Plan or required infrastructure improvements.
- 4. For those items listed with a TBD point value, please provide specific information and background studies (i.e. traffic study) for Staff to determine an assigned point value.
- 5. Submit the Screening Table along with the Planning Commission Review Application.

Residential Section

Feature	Description	Assigned Point Values	Project Points
Reduction N	Measure PS E1: Residential Energy Efficiency		
Building Env	velope		
Insulation	2019 Baseline (walls R-8:, roof/attic: R-30)	0 points	
	Enhanced Insulation (walls R-13:, roof/attic: R-38)	9 points	
	Enhanced Insulation (rigid wall insulation R-13, roof/attic: R-38)	9 points	
	Greatly Enhanced Insulation (spray foam wall insulated walls R-15 or higher, roof/attic R-38 or higher)	11 points	
Windows	2019 Baseline Windows (0.3 U-factor, 0.23 solar heat gain coefficient (SHGC)	0 points	
	Enhanced Window Insulation (0.28 U-Factor, 0.22 SHGC)	6 points	
	Enhanced Window Insulation (0.28 U-Factor, 0.22 SHGC)	7 points	
	Greatly Enhanced Window Insulation (0.28 or less U-Factor, 0.22 or less SHGC)	9 points	
Cool Roof	Enhanced Cool Roof (CRRC Rated 0.2 aged solar reflectance, 0.75 thermal emittance)	6 points	
	Enhanced Cool Roof (CRRC Rated 0.2 aged solar reflectance, 0.75 thermal emittance)	6 points	
	Greatly Enhanced Cool Roof (CRRC Rated 0.35 aged solar reflectance, 0.75 thermal emittance)	7 points	
Air Infiltration	Minimizing leaks in the building envelope is as important as the insulation properties of the building. Insulation does not work effectively if there is excess air leakage.		
	Air barrier applied to exterior walls, calking, and visual inspection such as the HERS Verified Quality Insulation Installation (QII or equivalent)	6 points	
	Blower Door HERS Verified Envelope Leakage or equivalent	5 points	
Thermal Storage of Building	Thermal storage is a design characteristic that helps keep a constant temperature in the building. Common thermal storage devices include strategically placed water filled columns, water storage tanks, and thick masonry walls.		
	Modest Thermal Mass (10% of floor or 10% of walls: 12" or more thick exposed concrete or masonry. No permanently installed floor covering such as carpet, linoleum, wood or other insulating materials)	1 points	
Building Envelope	Enhanced Thermal Mass (20% of floor or 20% of walls: 12" or more thick exposed concrete or masonry. No permanently installed floor covering such as carpet, linoleum, wood or other insulating materials)	2 points	
Performance Standard	Projects that have not been designed to a level of detail to know the specific attributes of the building envelope can use this option in committing to one of the following performance standards:		
	Modestly Enhanced Building Envelope (5% > Title 24)	12 points 28 points	
	Enhanced Building Envelope (15% > Title 24) Greatly Enhanced Building Envelope (20% > Title 24)	36 points	

Feature	Description	Assigned Point Values	Project Points
Indoor Space	e Efficiencies Residential		
Heating/	Minimum Duct Insulation (R-6 required)	0 points	
Cooling Distribution	Modest Duct insulation (R-8)	5 points	
System	Enhanced Duct Insulation (R-8)	5 points	
	Distribution loss reduction with inspection (HERS Verified Duct Leakage or equivalent)	7 points	
Space Heating/	2019 Minimum HVAC Efficiency (SEER 13/75% AFUE or 7.7 HSPF) Improved	0 points	
Cooling Equipment	Efficiency HVAC (SEER 14/78% AFUE or 8 HSPF)	2 points	
-4	High Efficiency HVAC (SEER 15/80% AFUE or 8.5 HSPF)	4 points	
	Very High Efficiency HVAC (SEER 16/82% AFUE or 9 HSPF)	5 points	
Water Heaters	2019 Minimum Efficiency (0.57 Energy Factor)	0 points	
	Improved Efficiency Water Heater (0.675 Energy Factor)	7 points	
	High Efficiency Water Heater (0.72 Energy Factor)	9 points	
	Very High Efficiency Water Heater (0.92 Energy Factor)	11 points	
	Solar Pre-heat System (0.2 Net Solar Fraction)	2 points	
	Enhanced Solar Pre-heat System (0.35 Net Solar Fraction)	5 points	
Daylighting	Daylighting is the ability of each room within the building to provide outside light during the day reducing the need for artificial lighting during daylight hours.		
	All peripheral rooms within the living space have at least one window (required)	0 points	
	All rooms within the living space have daylight (through use of windows, solar tubes, skylights, etc.) such that each room has at least 800 lumens of light during a sunny day	1 point	
	All rooms daylighted	1 point	
Artificial	2019 Minimum (required)	0 points	
Lighting	Efficient Lights (25% of in-unit fixtures considered high efficacy. High efficacy is defined as 40 lumens/watt for 15 watt or less fixtures; 50 lumens/watt for 15-40 watt fixtures, 60 lumens/watt for fixtures >40 watt)	5 points	
	High Efficiency Lights (50% of in-unit fixtures are high efficacy)	6 points	
	Very High Efficiency Lights (100% of in-unit fixtures are high efficacy)	7 points	
Appliances	Energy Star Refrigerator (new)	1 point	
	Energy Star Dish Washer (new)	1 point	

Feature	Description	Assigned Point Values	Project Points
	Energy Star Washing Machine (new)	1 point	
Miscellane	ous Building Efficiencies Residential		
Building Placement	North/South alignment of building or other building placement such that the orientation of the buildings optimizes natural heating, cooling, and lighting.	3 points	
Shading	At least 90% of south-facing glazing will be shaded by vegetation or overhangs at noon on Jun 21st.	2 Points	
Energy Star Homes	EPA Energy Star for Homes (version 3 or above)	15 points	
Other	This allows innovation by the applicant to provide design features that increases the energy efficiency of the project not provided in the table. Note that engineering data will be required documenting the energy efficiency of innovative designs and point values given based upon the proven efficiency beyond Title 24 Energy Efficiency Standards.	TBD	
Existing Residential Retrofits	The applicant may wish to provide energy efficiency retrofit projects to existing residential dwelling units to further the point value of their project. Retrofitting existing residential dwelling units within the City is a key reduction measure that is needed to reach the reduction goal. The potential for an applicant to take advantage of this program will be decided on a case by case basis and must have the approval of the Escondido Planning Department. The decision to allow applicants to ability to participate in this program will be evaluated based upon, but not limited to the following: Will the energy efficiency retrofit project benefit low income or disadvantaged residents? Does the energy efficiency retrofit project fit within the overall assumptions in Reduction Measure R2E3?		
	Does the energy efficiency retrofit project provide co-benefits important to the City?		
	Point value will be determined based upon engineering and design criteria of the energy efficiency retrofit project.	TBD	
Reduction I	Measure: New Home Clean Energy		
Photovoltaic	Solar Photovoltaic panels installed on individual homes or in collective neighborhood arrangements such that the total power provided augments:		
	30 percent of the power needs of the project	9 points	
	40 percent of the power needs of the project	12 points	
	50 percent of the power needs of the project	17 points	
	60 percent of the power needs of the project	20 points	

Feature	Description	Assigned Point Values	Project Points
	70 percent of the power needs of the project	23 points	
	80 percent of the power needs of the project	25 points	
	90 percent of the power needs of the project	28 points	
	100 percent of the power needs of the project	31 points	
Wind turbines	Some areas of the City lend themselves to wind turbine applications. Analysis of the area's capability to support wind turbines should be evaluated prior to choosing this feature. Individual wind turbines at homes or collective neighborhood arrangements		
	of wind turbines such that the total power provided augments:		
	30 percent of the power needs of the project	9 points	
	40 percent of the power needs of the project	12 points	
	50 percent of the power needs of the project	17 points	
	60 percent of the power needs of the project	20 points	
	70 percent of the power needs of the project	23 points	
	80 percent of the power needs of the project	25 points	
	90 percent of the power needs of the project	28 points	
	100 percent of the power needs of the project	31 points	
Off-site renewable energy project	The applicant may submit a proposal to supply an off-site renewable energy project such as renewable energy retrofits of existing homes that will help implement R2E4. These off-site renewable energy retrofit project proposals will be determined on a case by case basis and must be accompanied by a detailed plan that documents the quantity of renewable energy the proposal will generate. Point values will be determined based upon the energy generated by the proposal.	TBD	
Other Renewable Energy Generation	The applicant may have innovative designs or unique site circumstances (such as geothermal) that allow the project to generate electricity from renewable energy not provided in the table. The ability to supply other renewable energy and the point values allowed will be decided based upon engineering data documenting the ability to generate electricity.	TBD	

Feature	Description	Assigned Point Values	Project Points
Reduction M	leasure: Water Use Reduction Initiative		
Irrigation an	d Landscaping		
Water Efficient	Limit conventional turf to < 25% of each lot (required)	0 points	
Landscaping	Limit conventional turf to < 50% of each lot	2 points	
	Non-conventional turf warm season turf <50% of required landscape area and/or low-water using plants allowed)	4 points	
	Only California Native Plants that requires no irrigation or some supplemental irrigation	5 points	
Water Efficient	Low precipitation spray heads < .75"/hr or drip irrigation	1 point	
irrigation systems	Weather based irrigation control systems or moisture sensors (demonstrate 20% reduced water use)	2 points	
Recycled Water	Recycled connections (purple pipe) to irrigation system on site	6 points	
Water Reuse	Gray water Reuse System collects Gray-water from clothes-washers, showers and faucets for irrigation use	12 points	
Storm water Reuse Systems	Innovative on-site stormwater collection, filtration and reuse systems are being developed that provide supplemental irrigation water and provide vector control. These systems can greatly reduce the irrigation needs of a project. Point values for these types of systems will be determined based upon design and engineering data documenting the water savings.	TBD	
Potable Wat	ter Residential	1	
Showers	Water Efficient Showerheads (2.0 gpm)	2 points	
Toilets	Water Efficient Toilets (1.5 gpm)	2 points	
Faucets	Water Efficient faucets (1.28 gpm)	2 points	
Potable Water Performance Standard	Projects that have not been designed to a level of detail to know the specific attributes of the interior design of the buildings can use this option in committing to a potable water supply performance standard		
	EPA High Efficiency Water Fixtures (15% > Title 24)		
Reduction M	leasure: Land Use Based Trips and VMT Reduction		
Mixed Use Residential	Mixes of land uses that complement one another in a way that reduces the need for vehicle, determined based upon a Transportation Impact Analysis	TBD	
	Increased destination accessibility other than transit.	TBD	

Feature	Description		Assigned Point Values	Project Points
	Infill location that reduces vehicle trips or VMT beyond measures.	the specified	TBD	
Residential Near Local Retail	Having residential developments within walking and bil retail helps to reduce vehicle trips and/or vehicle miles value of residential projects in close proximity to determined based upon traffic studies that demonst and/or reductions in vehicle miles traveled (VMT)	traveled. The point local retail will be	TBD	
Other Trip Reduction Measures	Other trip or VMT reduction measures not listed abother traffic data supporting the trip and/or VMT for the	•	TBD	
Reduction M	easure: Bicycle Master Plan Development			
Bicycle	Provide bicycle paths within project boundaries.		TBD	
Infrastructure	Provide bicycle path linkages between residential and of	ther land uses.	2 points	
	Provide bicycle path linkages between residential and tr	ansit.	5 points	
Reduction M	leasure: Install EV Chargers			
Electric Vehicle	Level 1 110 volt AC chargers Per Cl	harger	2 points	
Recharging	Level 2 240 volt AC Fast Chargers Per Cl	harger	5 points	
Reduction M	leasure: Traffic Flow Management Improv	ements		
	Signal Synchronization		1 point	
	Signal connected to existing ITS		3 points	
Total Points Ear	ned by Residential Project:			

-Residential Section Ends-

Commercial/Industrial Section

Feature	Description	Assigned Point Values	Project Points
Reduction N	Measure PS E3: Energy Efficiency For Commercial Developme	nt	
Building En	velope		
Insulation	2019 baseline (walls R-16; roof/attic R-32)	0 points	
	Modestly Enhanced Insulation (walls R-15, roof/attic R-38)	9 points	
	Enhanced Insulation (rigid wall insulation R-13, roof/attic R-38)	11 points	
	Greatly Enhanced Insulation (spray foam insulated walls R-18 or higher, roof/attic R-38 or higher)	12 points	
Windows	2019 Baseline Windows (0.3 U-factor, 0.23 solar heat gain coefficient [SHGC)	0 points	
	Enhanced Window Insulation (0.28 U-factor, 0.22 SHGC)	4 points	
	Enhanced Window Insulation (0.28 U-factor, 0.22 SHGC)	4 points	
	Greatly Enhanced Window Insulation (0.28 or less U-factor, 0.22 or less SHGC)	5 points	
Cool Roofs	2019 Standard (none)	0 points	
	Enhanced Cool Roof (CRRC Rated 0.2 aged solar reflectance, 0.75 thermal emittance)	7 points	
	Enhanced Cool Roof (CRRC Rated 0.2 aged solar reflectance, 0.75 thermal emittance)	7 points	
	Greatly Enhanced Cool Roof (CRRC Rated 0.35 aged solar reflectance, 0.75 thermal emittance)	8 points	
Air Infiltration	Minimizing leaks in the building envelope is as important as the insulation properties of the building. Insulation does not work effectively if there is excess air leakage	0 points	
	Air barrier applied to exterior walls, calking, and visual inspection such as the HERS Verified Quality Insulation Installation (QII or equivalent)	7 points	
	Blower Door HERS Verified Envelope Leakage or equivalent	6 points	
Thermal Storage of Building	Thermal storage is a design characteristic that helps keep a constant temperature in the building. Common thermal storage devices include strategically placed water filled columns, water storage tanks, and thick masonry walls.		
	Modest Thermal Mass (10% of floor or 10% of walls 12" or more thick exposed concrete or masonry with no permanently installed floor covering such as carpet, linoleum, wood or other insulating materials)	2 points	
	Enhanced Thermal Mass (20% of floor or 20% of walls 12" or more thick exposed concrete or masonry with no permanently installed floor covering such as carpet, linoleum, wood or other insulating materials)	14 points	

Feature	Description	Assigned Point Values	Project Points
Building Envelope Performance Standard	Projects that have not been designed to a level of detail to know the specific attributes of the building envelope can use this option in committing to one of the following performance standards Modestly Enhanced Building Envelope (5% > Title 24) Enhanced Building Envelope (15% > Title 24) Greatly Enhanced Building Envelope (20% > Title 24)	TBD TBD TBD	
Indoor Space	e Efficiencies Commercial		
Heating/ Cooling Distribution System	Minimum Duct Insulation (R-6 required) Enhanced Duct Insulation (R-8) Enhanced Duct Insulation (R-8) Distribution loss reduction with inspection (HERS Verified Duct Leakage or equivalent)	0 points 5 points 5 points 6 points	
Space Heating/ Cooling Equipment	2019 Minimum HVAC Efficiency (EER 13/75% AFUE or 7.7 HSPF) Improved Efficiency HVAC (EER 14/78% AFUE or 8 HSPF) High Efficiency HVAC (EER 15/80% AFUE or 8.5 HSPF) Very High Efficiency HVAC (EER 16/82% AFUE or 9 HSPF)	0 points 4 points 5 points 7 points	
Commercial Heat Recovery Systems	Heat recovery strategies employed with commercial laundry, cooking equipment, and other commercial heat sources for reuse in HVAC air intake or other appropriate heat recovery technology. Point values for these types of systems will be determined based upon design and engineering data documenting the energy savings	TBD TBD	
Water Heaters	2019 Minimum Efficiency (0.57 Energy Factor)	0 points	
	Improved Efficiency Water Heater (0.675 Energy Factor)	8 points	
	High Efficiency Water Heater (0.72 Energy Factor)	10 points	
	Very High Efficiency Water Heater (0.92 Energy Factor)	11 points	
	Solar Pre-heat System (0.2 Net Solar Fraction)	2 points	
	Enhanced Solar Pre-heat System (0.35 Net Solar Fraction)	5 points	
Daylighting	All peripheral rooms within the customer areas have at least one window All rooms within the customer areas have daylight (through use of windows, solar tubes, skylights, etc.) such that each room has at least 800 lumens of light during a sunny day	0 points	
	All rooms daylighted	1 points	

Feature	Description	Assigned Point Values	Project Points
Artificial	2019 Minimum (required)	0 points	
Lighting	Efficient Lights (25% of in-unit fixtures considered high efficacy. High efficacy is defined as 40 lumens/watt for 15 watt or less fixtures; 50 lumens/watt for 15-40 watt fixtures, 60 lumens/watt for fixtures >40 watt)	5 points	
	High Efficiency Lights (50% of in-unit fixtures are high efficacy)	7 points	
	Very High Efficiency Lights (100% of in-unit fixtures are high efficacy)	8 points	
Appliances	Energy Star Commercial Refrigerator (new)	2 points	
	Energy Star Commercial Dish Washer (new)	2 points	
	Energy Star Commercial Cloths Washing Machine (new)	2 points	
Indoor Space Performance Standard	Projects that have not been designed to a level of detail to know the specific attributes of the interior design of the buildings can use this option in committing to one of the following performance standards		
	Modestly Enhanced Interior and appliances (5% > Title 24) Enhanced Interior and appliances (15% > Title 24) Greatly Enhanced Interior and appliances (20% > Title 24)	TBD TBD TBD	
Miscellaneo	us Commercial/Industrial Building Efficiencies	100	
Building Placement	North/South alignment of building or other building placement such that the orientation of the buildings optimizes natural heating, cooling, and lighting.	4 points	
Shading	At least 90% of south-facing glazing will be shaded by vegetation or overhangs at noon on Jun 21st.	6 points	
Other	This allows innovation by the applicant to provide design features that increases the energy efficiency of the project not provided in the table.		
	Engineering data will be required documenting the energy efficiency of innovative designs and point values given based upon the proven efficiency beyond Title 24 Energy Efficiency Standards.	TBD	
Existing Commercial Retrofits	The applicant may wish to provide energy efficiency retrofit projects to existing Commercial dwelling units to further the point value of their project. Retrofitting existing Commercial dwelling units within the City is a key reduction measure that is needed to reach the reduction goal. The potential for an applicant to take advantage of this program will be decided on a case by case basis and must have the approval of the Escondido Planning Department. The decision to allow applicants to ability to participate in this program will be evaluated based upon, but not limited to the following:		
	Will the energy efficiency retrofit project benefit low income or disadvantaged residents? Does the energy efficiency retrofit project fit within the overall		
	assumptions in Reduction Measure R2E3?		

Feature	Description	Assigned Point Values	Project Points
	Does the energy efficiency retrofit project provide co-benefits important to the City?		
	Point value will be determined based upon engineering and design criteria of the energy efficiency retrofit project.	TBD	
Reduction	Measure PS E2: New Commercial/Industrial Renewable End	ergy	
Photovoltaic	Solar Photovoltaic panels installed on commercial buildings or in collective arrangements within a commercial development such that the total power provided augments:		
	30 percent of the power needs of the project	8 points	
	40 percent of the power needs of the project	12 points	
	50 percent of the power needs of the project	16 points	
	60 percent of the power needs of the project	19 points	
	70 percent of the power needs of the project	23 points	
	80 percent of the power needs of the project	26 points	
	90 percent of the power needs of the project	30 points	
	100 percent of the power needs of the project	34 points	
Wind turbines	Some areas of the City lend themselves to wind turbine applications. Analysis of the area's capability to support wind turbines should be evaluated prior to choosing this feature.		
	Individual wind turbines at homes or collective neighborhood arrangements of wind turbines such that the total power provided augments:		
	30 percent of the power needs of the project	8 points	
	40 percent of the power needs of the project	12 points	
	50 percent of the power needs of the project	16 points	
	60 percent of the power needs of the project	19 points	
	70 percent of the power needs of the project	23 points	
	80 percent of the power needs of the project	26 points	
	90 percent of the power needs of the project	30 points	
	100 percent of the power needs of the project	34 points	
Off-site renewable energy project	The applicant may submit a proposal to supply an off-site renewable energy project such as renewable energy retrofits of existing Commercial that will help implement R2 E4, or existing commercial/industrial that will help implement R2 E7. These off-site renewable energy retrofit project proposals will be determined on a case by case basis accompanied by a detailed plan documenting the quantity of renewable energy the proposal will generate.		
	Point values will be determined based upon the energy generated by the proposal.	TBD	

Feature	Description	Assigned Point Values	Project Points
Other Renewable Energy Generation	The applicant may have innovative designs or unique site circumstances (such as geothermal) that allow the project to generate electricity from renewable energy not provided in the table. The ability to supply other renewable energy and the point values allowed will be decided based upon engineering data documenting the ability to		
	generate electricity.	TBD	
Reduction N	leasure PS W2: Water Use Reduction Initiative		<u> </u>
Irrigation ar	nd Landscaping		
Water Efficient	Eliminate conventional turf from landscaping	0 points	
Landscaping	Only moderate water using plants	2 points	
	Only low water using plants	3 points	
	Only California Native landscape that requires no or only supplemental irrigation	5 points	
Water Efficient	Low precipitation spray heads< .75"/hr. or drip irrigation	1 point	
Irrigation Systems	Weather based irrigation control systems combined with drip irrigation (demonstrate 20 reduced water use)	3 points	
Recycled Water	Recycled water connection (purple pipe) to irrigation system on site	5 points	
Trees	Increase tree planting in parking areas 50% beyond City Code requirements	TBD	
Storm water Reuse Systems	Innovative on-site stormwater collection, filtration and reuse systems are being developed that provide supplemental irrigation water and provide vector control. These systems can greatly reduce the irrigation needs of a project.		
	Point values for these types of systems will be determined based upon design and engineering data documenting the water savings.	TBD	
Potable Wa	ter Commercial		
Showers	Water Efficient Showerheads (2.0 gpm)	2 points	
Toilets	Water Efficient Toilets/Urinals (1.5gpm)	3 points	
	Waterless Urinals (note that commercial buildings having both waterless urinals and high efficiency toilets will have a combined point value of 6 points)	3 points	
Faucets	Water Efficient faucets (1.28gpm)	2 points	
Commercial Dishwashers	Water Efficient dishwashers (20% water savings)	2 points	

Feature	Description	Assigned Point Values	Project Points
Commercial Laundry Washers	EPA Water Efficient laundry (15% water savings)	2 points	
	EPA High Efficiency laundry Equipment that captures and reuses rinse water (30% water savings)	4 points	
Commercial Water Operations Program	Establish an operational program to reduce water loss from pools, water features, etc., by covering pools, adjusting fountain operational hours, and using water treatment to reduce draw down and replacement of water.		
	Point values for these types of plans will be determined based upon design and engineering data documenting the water savings.	TBD	
Potable Water Performance Standard	Projects that have not been designed to a level of detail to know the specific attributes design can use this in committing to a potable water efficiency	TBD	
Reduction M	leasure: Land Use Based Trips and VMT Reduction		
Mixed Use Commercial	Mixes of land uses that complement one another in a way that reduces the need for vehicle trips can greatly reduce GHG emissions. The point value of mixed use projects will be determined based upon a Transportation Impact Analysis (TIA) demonstrating trip reductions and/or reductions in vehicle		
	miles traveled. Suggested ranges:	TBD	
	Mixes of land uses that complement one another in a way that reduces the need for vehicle, determined based upon a Transportation Impact Analysis (2-28 points)	TBD	
	Increased destination accessibility other than transit (1-18 points)	TBD	
	Increased transit accessibility (1-28 points)	TBD	
	Infill location that reduces vehicle trips or VMT beyond the specified measures	TBD	
Local Retail Near Residential (Commercial only Projects)	Having residential developments within walking and biking distance of local retail helps to reduce vehicle trips and/or vehicle miles traveled.		
	The point value of residential projects in close proximity to local retail will be determined based upon traffic studies that demonstrate trip reductions and/or reductions in vehicle miles traveled.	TBD	
	Preferential parking	1 point	
	Synchronize signals	1 point	
	Connect signals to existing ITS	3 points	
Reduction M	leasure: Bicycle Master Plan Development		_
Bicycle Infrastructure	Provide bicycle paths within project boundaries.	1 point	
	Provide bicycle path linkages between residential and other land uses.	2 points	
	Provide bicycle path linkages between residential and transit.	5 points	

Feature	Description	Assigned Point Values	Project Points		
Reduction Measure: Electric Vehicle Infrastructure					
Cars	Level 2 240 volt AC Fast Chargers	5 points			
	Level 3 480 volt DC Rapid Chargers	8 points			
Trucks	Medium & Heavy Duty Electric Truck Chargers				
Trucks	Level 1 AC Chargers for EV Medium Duty Truck	3 points			
	Level 1 AC Chargers for EV Class 8 (Heavy Duty) Truck	5 points			
	Level 2 AC Chargers for EV Medium Duty Truck	8 points			
	Level 2 AC Chargers for EV Class 8 (Heavy Duty) Truck	12 points			
	Level 3 DC Chargers for EV Class 8 (Heavy Duty) Truck	16 points			
Total Points from	n Commercial/Industrial Project:				

⁻Commercial/Industrial Section Ends-